



D200 CONTACTLESS MPOS

- **Contactless, Chip, Magstripe**
- **iOS & Android Compatible**
- **Visa & MasterCard NFC**
- **WCDMA, GPRS, Bluetooth, WiFi**
- **Color Touch Screen**
- **Apple MFi approved**
- **PCI PTS 4.x, SRED**

PAX's beautifully designed D200 integrates with any mobile payment app running on iOS or Android smart device via Bluetooth, WiFi, WCDMA, GPRS or cable connection. The D200 offers the latest PCI PTS 4.x security, SRED and Visa payWave & MasterCard Contactless certification. Apple Inc. has given the D200 a special certification called MFi meaning that Apple has tested and approved the D200 to meet the highest performance standards for integration with any iPad or iPhone, including the new iPhone 7.

www.paxglobatechnology.com

Your Payment Partner of Choice



D200 CONTACTLESS MPOS

Features & Benefits



High Reliability & Exceptional Performance

- Contactless NFC, EMV chip and magstripe enabled
- Featuring innovative touch-press key design
- Stylishly designed for comfort and convenience
- Colour touch screen with user friendly interface
- Large memory capacity

Flexible Platform

- Bluetooth, WiFi, WCDMA, GPRS
- USB port for high speed data transmission
- Versatile Operating System

Unprecedented Security

- PCI PTS 4.x approved, SRED
- Secure key embedded area

Specifications

Processor

32-bit ARM 11

Memory

192MB (128MB Flash, 64MB SDRAM)

Display

2.4 inch TFT colour LCD, 320 x 240 pixels
Touch screen (optional)

Keypad

Touch- button input
10 numeric & 5 function keys

Magnetic Card Reader

Track1 / 2 / 3, Bi-directional

Smart Card Reader

EMV L1 & L2 certified

Contactless Card Reader

MasterCard Contactless & Visa payWave
ISO14443 Type A/B
Mifare®, Felica, NFC

Card slots

2 SAMs
or 1 SAM & 1 SIM (GPRS)

Communication

WCDMA / GPRS +/- (WiFi+Bluetooth)

Peripheral Ports

1 x Micro USB
1 x RS232

Security

PCI PTS 4.x certified
SRED

Environmental

0°C to 50°C (32°F to 122°F) operating temperature
-20°C to 70°C (-4°F to 158°F) storage temperature
10% to 93% relative humidity, non-condensing

Voltage

Battery, 3.7V, 1900mAh
Input: 100 - 240V AC, 50 / 60 Hz, 0.2A
Output: 5VDC, 1A

Physical

Length: 121mm
Width: 72mm
Height: 22.5mm

Weight

165 g with battery

Certifications

PCI PTS 4.x, SRED
EMV Contact L1 & L2
EMV Contactless L1
Visa payWave
MasterCard Contactless
AMEX Expresspay
Discover D-PAS
JCB J/Speedy
MasterCard TQM
Visa Ready
MasterCard MPOS

www.paxglobatechnology.com